



Item	See Page
Rustless	36 40 42
SLR Self-Lube Chain	51
MF Maintenance Free	56 76
Drive Chain Selection	76 77

	32B
	68P 60P
Unit (5m)	114P P

28B

SY Chain No. (B S)	Pitch	Dimensions - mm											Minimum Ultimate Strength	Maximum Allowable Load	Average Chain Weight
		Roller		Pin				Plate		Trans. Pitch					
		Width	Dia.	Dia.	Length		Height	Thickness							
P	W	R	D	LR	LC	L1	L2	H	T1	T2	TP	kN	kN	kg/m	
28B	44.45	31.00	27.94	15.88	65.1	70.5	32.6	37.9	37.0	6.3	7.4	59.56	200	44.5	9.26
-2					124.7	130.0							360	58.3	18.45
-3					184.2	189.6							530	85.8	27.65

32B

SY Chain No. (B S)	Pitch	Dimensions - mm											Minimum Ultimate Strength	Maximum Allowable Load	Average Chain Weight
		Roller		Pin				Plate		Trans. Pitch					
		Width	Dia.	Dia.	Length		Height	Thickness							
P	W	R	D	LR	LC	L1	L2	H	T1	T2	TP	kN	kN	kg/m	
32B	50.80	31.00	29.21	17.81	65.0	71.1	32.5	38.6	42.2	6.3	6.9	58.55	250	51.0	9.92
-2					123.4	129.7							450	66.6	19.76
-3					182.0	188.3							670	98.0	29.61

Refer to page 80. " Selection of offset link "

info@adeptrans.es